BASE-6



BASE-6 is an all-weather 2-way wall-mounted speaker system with a 6.5'' low-middle range woofer and a 1'' high frequency tweeter. Has an effective power output of up to 40W RMS. Equipped with a 100-volt linear transformer with power taps of 2.5, 5, 10, 20 and 40 W. Case color black or white

- All weather loudspeakers for music applications and projects.
- Ideal for indoor outdoor BGM and paging system
- IP66 waterproof finish for all extreme weather applications
- 6.5" weatherproof woofer and 1” silk tweeter 2-way speaker system
- ABS enclosure, stainless metal grille & stainless mounting bracket
- Power output 40-20-10-5-2.5W & 8Ω
- 70V/100V speaker with power tapping or as a low impedance 8 Ohm speaker
- Waterproof cable wiring cover for IP66 secure weatherproof protection
- Ultra- reliable, fail safe loudspeaker even at high power loads
- Supplied with 360° rotatable bracket for horizontal and vertical installation angle adjustment

Specification:

SKU	**BASE-6**
Type	Wallmount Speaker
Rated Power	40W at 8Ohm/100V/70V (max. 60W)
Input Options	8Ohm / 100V/ 70V
Transformer Taps100V	2.5W / 5W / 10W / 20W / 40W
Ways	2
Drivers	6.5" weatherproof woofer
	1” silk tweeter
Effective frequency range	60 - 20KHz
Sound Pressure Level	112dB
Sensitivity	94dB, measured at 1W/m
Waterproof degree	IP66
Material	ABS enclosure, stainless metal grille & stainless mounting bracket
Dispersion	Vertical: 180° and Horizontal: 180° (1KHz)
Finished colour	White (BASE-6W), Black (BASE-6B)
Mounting bracket	Included
Dimension	150x180x280 mm (without bracket)
Weight	3.6kg





Mounting Bracket





