RUNA-6T







RUNA-6T - is a frameless ceiling 2-way loudspeaker featuring a 6.5” low frequency driver and 0.75” rotating tweeter. Has an effective power output of up to 40W RMS. Equipped with a 100V line transformer with 5, 10, 20 and 40 W power taps. The frameless design ensures is the best choice for modern building installation. Thanks to hi-flex polypropylene cone for the low and middle range and high frequency tweeter the speaker is ideal for background music, paging system and other applications. The speaker baffle can made of robust ABS plastic for better low frequency sounds. Entire construction makes it suitable for different ceiling heights for indoor installations. Flash mount and magnetic grill fix make installation and maintenance fast and simple.

Polar Diagram and Frequency Response:



SPL vs Freq



Specification:

SKU	**RUNA-6T**
Type	Ceiling Speaker
Rated Power	40W at 8Ohm/100V
Input Options	8Ohm / 100V
Transformer Taps	5W / 10W / 20W / 40W / 8Ohm
Ways	2
Drivers	6.5” low-middle range woofer
	0.75” high frequency tweeter
Effective frequency range	80 - 20KHz
Sound Pressure Level	103dB
Sensitivity	89dB, measured at 1W/m
Connection type	Phoenix Terminal 4-pin
Baffle	Black ABS
Grille	Steel, magnet fixing
Finished colour	White
Mounting options	In ceiling, cutout Ø218mm
Dimension (ØxD)	240×93mm
Weight	1.6kg